



Fiber optic flat cable Telcoline FTTH 2J (black, LSZH) REINFORCED 1000m



link to the product:

<https://intersell.pl/gb/1027-light-cable-flat-telcoline-ftth-2j-black-lszh-reinforced-1000m.html>

Manufacturer: Telcoline

Referention number: TEL-FLAT-2J+

Full product description

Fiber optic cable Telcoline FTTH 2J is a cable suitable for both indoor and outdoor applications (UV resistant, wide range of acceptable ambient temperature). The cable contains two ARP (Aramid Reinforced Polymer) rods embedded in the outer layer, which strengthen the cable and protect the fibers from damage. The cable has **aramid reinforcement**.

G.657A1 fibers fully comply with the G.652D standard.

SPECIFICATION

Technical parameters	
Fiber type	G.657A1
Number of fibers	2
Attenuation [dB / km]	For 1310nm: <0.34 For 1550nm: <0.21
Crush resistance	2000N / 100mm
Outer shell	LSZH (Low Smoke Zero Halogen) Resistant to UV radiation Black colour
Minimum bending radius [mm]	10
Destiny	Outdoor installations Internal installations
General parameters	
Dimensions (width x thickness) [mm]	3 x 2
Weight [kg / km]	10

Working conditions	Ambient temperature: -20 to 60 [° C]
--------------------	--------------------------------------