Sosnowa 2B 55-300 Szczepanów tel: +48 71 307 07 55



Ftth 2J Telcoline fiber optic cable (white, LSZH) 1000m





link to the product:

 $\frac{\text{https://intersell.pl/gb/1028-light-cable-plastic-telcoline-ftth-2j-white-lszh-1000m-5907813980886}{\text{html}}$

Manufacturer: Telcoline

Referention number: TEL-FLAT-2J-B

Information:

ARP rod-reinforced fiber optic cable, suitable for both outdoor and indoor applications. Number of fibres: 2. Fibre type: G.657A1 (compatible with G.652D). Weight: 10 kg/km.



Full product description

Fiber optic cable Telcoline FTTH 2J is a cable suitable for both indoor and outdoor applications (resistant to UV rays, wide range of permissible ambient temperature). The cable contains two ARP (Aramid Reinforced Polymer) rods embedded in the outer layer, which strengthen the cable and protect the fibers from damage. G.657A1 fibers fully comply with the G.652D standard.

SPECIFICATION

Technical parameters	
Fiber type	G.657A1
Number of fibers	2
Attenuation [dB / km]	For 1310nm: <0.34 For 1550nm: <0.21
Crush resistance	2000N / 100mm
Outer shell	LSZH (Low Smoke Zero Halogen) Resistant to UV radiation White color
Minimum bending radius [mm]	10
Destiny	Outdoor installations Internal installations
General parameters	
Dimensions (width x thickness) [mm]	3 x 2
Weight [kg / km]	10
Working conditions	Ambient temperature: -20 to 60 [° C]

6-10-2025