

OCI-20B Video connector and adapter inspector, USB connector, LCD display, video memory



link to the product:

 ${\color{blue} https://intersell.pl/gb/936-oci-20b-video-inspector-connectors-and-adapters-usb-display-lcd-memory-video.html}$

Manufacturer: ShinewayTech
Referention number: OCI-20B



Full product description

OCI-20B Optical Connector Inspector

- U Compatible with various connectors
- $\ensuremath{\textbf{U}}$ Dual channel video input (microscope) for easy viewing of male / female connectors
- U Extended display on external monitor
- U Audio & video recording
- U Multimedia playback
- U Direct read / write flash disk
- U Large storage: 128MB internal memory, SD card up to 16GB
- U Data transfer via USB2.0
- $\color{red}\textbf{U}$ Internal battery for 9 hours continuous operation
- U Compact & lightweight

OCI-20B is a portable optical fiber connector inspector for checking fiber and connector end-face cleanliness, ideal for bench top and fiber optic network installation technicians to eliminate error caused by poor quality or improper cleaning.

OCI-20B offers excellent viewing on connector / fiber end-face and has a unique feature to record and save image / video of fiber end-face all by itself, with no computer or any external devices needed, which is the only type of its kind in the industry.



Specifications

opecine acionis	
Model	OCI-20B
Field of Vision	300 × 280μm
Zoom	Scope: 600X (12X Optical zoom); Display: 200X
Resolution	0.5μm
Focus	Manual adjustment
Sensor	1 / 3IN CCD, black & white
Display	2.5 inch LCD (960 × 240)
Video / Audio Recording	Yes (Video with timing display)
Video Input	Dual channels: CH1 / CH2 (2 ports)
Audio Output	Earphone jack: L 20mW + R 20mW [160] (Max volume)
Storage	128MB internal, SD card storage up to 16GB
Connector	SC / FC / LC / E2000 / MU / ST etc. (PC / APC, male & female)
Connectivity	USB / Card Reader (SD / MMC)

6-10-2025

Power Supply	Lithium battery (1800mAh) / Power Adapter (DC 5V, 2A)
Battery Life	? 9 hours (continuous operation)
Weight	170g
Dimensions (H × W × T)	162 × 96 × 40mm

6-10-2025